

Bill of Quantities (Changes 31.08.2020.)

Removal of obstacles for persons with disabilities and investment maintenance of the halls in National Museum Leskovac, at KP 5418, KO Leskovac.

area code	Description of works	Unit of measure	Quantity	price per unit	Total
7.00	<u>CERAMIC AND SUPPORTING WORKS</u>				
7.04.	<p>Procurement and installation of floor granite ceramics and ceramics should be done on the fronts, steps, steps and part of the floor in front of the toilet.</p> <p>Coating part of the floor, front and treads of the steps with granite ceramics would be in the price class up to 2400 dinars without VAT, or similar according to the designer's choice, on glue of the appropriate type for this type and dimension of tiles. Lay the tiles according to the joint-on-joint system. Prepare the substrate beforehand and lay it flat. At the junction of the forehead and the tread, place a metal strip Schluter SCHIENE STEP, or similar at the choice of the designer. Clean the installed tiles with sawdust. The price also includes the purchase of ceramics. Calculation will be done per m². Measures will be taken on the spot.</p>	m ²	54.00 x	=	

area code	Description of works	Unit of measure	Quantity	price per unit	Total
10.00	ALUMINUM AND GLAZIERS WORKS				
10.01.	<p>Aluminum entrance portal.</p> <p>Procurement and installation of an entrance portal with double doors will be made of aluminum profiles from the Alumil M50 system, RAL 7016, or another manufacturer, with overall dimensions of 740 x 250cm.</p> <p>It is consisted of load-bearing vertical and horizontal aluminum profiles with, thermal break width, 50 mm and depth in the vertical direction of 150 mm and in the horizontal direction of 50 mm. The glass package is mounted on the outside using special profiles 50 mm wide, which are covered with cover profiles 50 mm wide and 16 mm deep. The door on the portal is from aluminum profile with thermal break. The door handles go the entire height of the door, in a design chosen by the designer.</p> <p>The side parts between the portal and the walls must be made of steel box profiles lined with alubond in the color RAL 7016. Inside these boxes, should be placed 15 cm thick mineral wool. The dimensions of these elements are 16 x 16 x 250 cm. The overall dimensions of the portal with side edging are 770 x 250cm. The portal is glazed with glass package 3.3.1 (outside) + 15 + 6 mm, with internal low-emission glass. Calculation will be done per piece.</p>				
10.02.	<p>Glazing of existing fixed portals with installation of decorative moldings. Double glazed glazing 6 + 15 + 4 (mm). The inner glass is low emission. Place the thermal glass on stainless steel coasters (lead, wood, plastic material) during installation. Putty with a suitable plastic putty, the metal frame of the thermo glass must not be visible. It is necessary to procure and install new aluminum decorative moldings, at the choice of the designer, on the inside of the portal. Calculation will be done per month.</p>	kom.	1 x		=
		m ²	47.0 x		=

area code	Description of works	Unit of measure	Quantity	price per unit	Total
10.03.	Internal aluminum glazed door portals with doors. Production, transport and installation of internal portal from Al profiles, plasticized in RAL 7016 tons. Construction without thermal break. Glass glazing 3.3.1 mm. Match the cross-sectional shape of the profile with the entrance portal. The price includes complete hardware (hinges and locks). Material, workmanship, details, fittings in everything according to the manufacturer's technology, and with the approval of the designer and supervision. Calculation will be done per month.				
		m ²	12.0 x	=	
10.04.	Procurement, production and installation of a glass fence should be done in the ELEGANT AL50 system, or equivalent. The fence consists of 74 steel matt chrome glass girders anchored in the concrete parapet of the fence and tempered glass panels, 12 mm thick, with a total area of 35 m ² . Position implies all the necessary material. Calculation will be done per m of a completely installed fence.				
	/ oblique	m ¹	18.5 x	=	
	/ horizontal	m ¹	7.2 x	=	
				Σ =	
10.05.	Procurement and installation should be made of interior doors. MDF wing covered with PVC foil of the designer's choice. Calculation will be done per piece of door.				
	/ 90x220	kom.	4 x	=	
	/ 100x220	kom.	1 x	=	
				Σ =	

08.2020.

chief designer:



dia Vladan Nikolić